

# SEALFIX

## PENETRATING SEALER FOR TILE JOINTS

INFRA SEALFIX is the answer to sealing leaks in shower alcoves and other tiled areas easily, without any hassle of removing and replacing tiles. INFRA SEALFIX prevents moisture from getting behind tiles which can cause dampness in adjoining walls / slabs, lifting of tiles, mould, damage to surrounding timber, and electrical problems.

INFRA SEALFIX is a siloxane solvent based material that forms a water-repellant barrier in grout and porous tiles by penetrating deep into the matrix of the substrates. By its penetrating action, SEALFIX is a permanent coating that does not get damaged when scratched or chipped by ordinary cleaning. Its sealant properties are within the matrix of the grout and/or porous tiles, eliminating the need for constant reapplication for it to be effective.

### Features & Advantages

- Clear and colourless liquid
- No further mixing required
- Direct easy application
- Penetrates grout and porous tiles, but still allows it to breathe
- Resistant to minor scratches and chips from ordinary cleaning
- Eliminates the need to remove tiles for waterproofing.

### Coverage

Coverage based on 1 coat application:

30 sqm per 1000ml

(or 322sq. ft. per litre)

### Packaging

Product is available in sealed 1000ml bottles.

### Performance

Moisture metre tests showed no moisture passing through areas that are sealed.

### Application

**Step 1:** Clean shower and grout thoroughly to remove any laitance, oils and foreign matter and expose clean bare grout;

**Step 2:** Remove grout or sealant from vertical and horizontal corners to refill later with colour seal. Re-point all other cracked or damaged grout. Allow at least 24hrs for new grout to cure prior to SealFix treatment.

**Step 3:** Ensure all surfaces are visually dry and mould free. Apply 2 coats of INFRA SEALFIX liberally with a brush, paying attention to grout lines, wet on wet. Allow approximately 5mins before wiping off excess with a soft cloth. Allow 24 hrs before using the shower.

**Step 4:** Cove the junction of floor/wall and wall/wall joints with colour seal.

Mineral turps can be used to clean up dried SealFix.

### Safety

SealFix contains flammable solvents - do not expose to naked flames, electrical equipment or smoke. Ensure adequate ventilation during application and drying periods. Avoid direct contact with skin or eyes by wearing protective gloves and goggles during application. Do not induce vomiting if swallowed - give a glass of water and contact a doctor or your local poisons information centre for help.